

01512-1004

CHARTPAK INC.
1 River Road
Leeds, MA 01053
Phone: 413.584.5446
FAX: 1-413.587.0499
Email: INFO@chartpak.com

In the event of a transportation emergency, call CHEMTRECS at (01) 703-527-3887

For health emergencies, call the Poison Control Center at 1-800-222-1222

SECTION I - IDENTIFICATION

Material Name

GRUMBACHER SYNVAR

Company Information

CHARTPAK INC.
1 River Road
Leeds, MA 01053
Phone: 413-584-5446
Fax: 413-587-0499
Email: INFO@chartpak.com

For transportation emergencies only call: 888-786-0972

For health emergencies call the Poison Control Center: 1-800-222-1222

SECTION II - HAZARDS IDENTIFICATION

Classification in accordance with paragraph (d) of 29 CFR 1910.1200.

Aspiration Hazard - Category 1
Flammable Liquid 2
Flammable Liquid 3

GHS Label Elements

Symbol(s)



Signal Word(s)

Danger

Hazard Statement(s)

Flammable liquid and vapour May be fatal if swallowed and enters airways.

Precautionary Statement(s)

Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Keep cool. Ground and bond container and receiving equipment. Use explosion-proof equipment. Use non-sparking tools. Take action to prevent static discharges. Wear protective gloves/protective clothing/eye protection/face protection. Store in a well-ventilated place. Store locked up.

Response

Do NOT induce vomiting. Rinse skin with water [or shower]. Take off immediately all contaminated clothing. IF

SWALLOWED: Immediately call a POISON CENTER/doctor.

SECTION III - HAZARDOUS INGREDIENTS

| Hazardous Ingredients | CAS/EC # | PEL/TLV (MG/M#) | Max % Weight | NTP | IARC |
|------------------------------|-----------------|----------------------------|-------------------------|------------|-------------|
| PETROLEUM DISTILLATES | | 525.00 | 76.56364 | N | N |
| STODDARD SOLVENT | 232-489-3 | N/A | 51.92000 | N | N |
| ETHANOL | 64-17-5 | N/A | 6.14000 | N | N |

SECTION IV - FIRST AID MEASURES

FIRST AID MEASURES: If eye contact occurs, rinse with tap water for 5-10 minutes. If irritation persists, seek medical care. If swallowed, do not induce vomiting. Call a physician or poison control center immediately. If inhalation symptoms occur, move to fresh air. If symptoms persist, see a physician. If skin contact occurs, wash with soap and water for 5 minutes. If swallowed, get prompt medical attention.

SECTION V - FIRE FIGHTING MEASURES

FLASH POINT (METHOD): 105° F (40° C) AUTOIGNITION TEMPERATURE: N/A
 EXPLOSION LIMITS IN AIR (% BY VOLUME): LEL 0.5% - UEL 6%
 EXTINGUISHING MEDIA: Foam, CO2, Dry Chemical (Class B) or Halon
 FIRE FIGHTING PROCEDURES: NO SPECIAL FIRE FIGHTING PROCEDURES REQUIRED
 Wear self-contained breathing apparatus.
 UNUSUAL FIRE & EXPLOSION HAZARDS: FLAMMABLE. FLAMMABLE

SECTION VI - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE A MATERIAL IS SPILLED: Clean up in accordance with all applicable regulations. Absorb spillage with non-combustible, absorbent material. For waste disposal, see Section XIII

SECTION VII - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN DURING STORAGE AND HANDLING: Good industrial hygiene practice requires that exposure be maintained below the TLV. This is preferably achieved through the provision of adequate ventilation. When exposure cannot be adequately controlled in this way, personal respiratory protection should be employed.

SECTION VIII - EXPOSURE CONTROLS / PERSONAL PROTECTION

RESPIRATORY PROTECTION AND SPECIAL VENTILATION REQUIREMENTS: Use only with adequate ventilation.
 OTHER PROTECTIVE EQUIPMENT (GLOVES, GOGGLES, ETC): When using wear impermeable protective gloves.
 WORK/HYGIENE PRACTICES: Avoid prolonged contact with skin. Wash hands immediately after use. Avoid ingestion.
 ENGINEERING CONTROLS: Do not store or use near heat or flame.

FOR HOME USE: CHILD-PROOF PACKAGING REQUIRED IN CONFORMANCE WITH 16CFR1700.15 a), b), and c) and meet the child test protocol requirements of one of CSA-Z76.1, ISO 8317 or 16 CFR 1700.20 or a standard that is at least equivalent.
KEEP OUT OF REACH OF CHILDREN.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: >300°F (>149°C)
VAPOR PRESSURE: 6mm Hg
SPECIFIC VAPOR DENSITY (AIR=1): N/A
SOLUBILITY IN WATER: N/A

MELTING POINT: N/A
FLASH POINT (METHOD): 105° F (40° C)
SPECIFIC GRAVITY: 0.83
REACTIVITY IN WATER: NON-REACTIVE

SECTION X - STABILITY AND REACTIVITY

HAZARDOUS POLYMERIZATION PRODUCTS: N/A
STABILITY: STABLE CONDITIONS TO AVOID: N/A
INCOMPATIBILITY (MATERIALS TO AVOID): N/A
HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide and smoke

SECTION XI - TOXICOLOGICAL INFORMATION

ACUTE EFFECTS ASSOCIATED WITH USE OF THIS MATERIAL: SKIN IRRITANT. EYE IRRITANT. EXPOSURE MAY RESULT IN NAUSEA, HEADACHE, CONFUSION OR INSTABILITY. HARMFUL OR FATAL IF SWALLOWED. VAPOR HARMFUL. CONTACT MAY RESULT IN IRRITATION OF THE SKIN.

The summated LD50 is >50000 mg/kg.
The summated LC50 is 99999 mg/cubic meter.
This product is not considered to be a known or suspected human carcinogen by NTP, IARC or OSHA (see section III)

SECTION XII - ECOLOGICAL INFORMATION

HARMFUL EFFECTS KNOWN OTHER THAN THOSE ASSOCIATED WITH SUSPENDED INERT SOLIDS IN WATER.

SECTION XIII - DISPOSAL CONSIDERATIONS

RCRA HAZARD CLASS (40 CFR 261): THIS PRODUCT IS NOT CLASSIFIED AS A HAZARDOUS WASTE.
WASTE DISPOSAL METHOD: DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

SECTION XIV - TRANSPORTATION INFORMATION

U.S. D.O.T. Ground Transportation: Not Regulated Ocean Transportation: UN 1263 Paint Related Material, Class 3, PG III, Limited Quantity
DO NOT SHIP via air freight without special packaging and labeling. Contact your air carrier for detailed instructions.

SECTION XV - REGULATORY INFORMATION

CONTENTS OF THIS SDS COMPLY WITH OSHA HAZARD COMMUNICATION STANDARD 29 CFR 1910.1200

EPA SARA TITLE III CHEMICAL LISTINGS:
SECTION 302.4 EXTREMELY HAZARDOUS SUBSTANCES (40 CFR 355):
NONE

SECTION 313 TOXIC CHEMICALS (40 CFR 372):
MINERAL SPIRITS MIXTURE

INTERNATIONAL REGULATIONS

CANADIAN WHMIS: THIS PRODUCT IS A CONTROLLED PRODUCT UNDER CANADA'S WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM. IT CONTAINS THE FOLLOWING TOXIC OR HIGHLY TOXIC MATERIALS:
ETHYL ALCOHOL
MINERAL SPIRITS MIXTURE

STODDARD SOLVENT

Under CPSC's consumer product regulations (16CFR1500.3 and 150014), this product has the following required acute and chronic hazard labeling:

DANGER: FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. VAPOR HARMFUL. SKIN IRRITANT. EYE IRRITANT.
Contains: PETROLEUM DISTILLATES

PRECAUTIONS: Avoid prolonged contact with skin. Wash hands immediately after use. When using wear impermeable protective gloves. Avoid ingestion. Do not store or use near heat or flame. Use only with adequate ventilation. **KEEP OUT OF REACH OF CHILDREN.**

FIRST AID TREATMENT: If eye contact occurs, rinse with tap water for 5-10 minutes. If irritation persists, seek medical care. If swallowed, do not induce vomiting. Call a physician or poison control center immediately. If inhalation symptoms occur, move to fresh air. If symptoms persist, see a physician. If skin contact occurs, wash with soap and water for 5 minutes. If swallowed, get prompt medical attention.

This adult product is certified to comply with the Consumer Product Safety Act (CPSA), the Poison Prevention Packaging Act, the Federal Hazardous Substances Act, (FHSA) and its Labeling for Hazardous Art Materials Act (LHAMA).

SECTION XVI - OTHER INFORMATION

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

LAST REVISION DATE: 01/29/2021

Prepared by Duke OEM Toxicology

BRAND NAMES

THIS SDS APPLIES TO THE FOLLOWING BRAND NAMES

| Brand Name | SKU | SKU Description |
|----------------------------------|----------------|------------------------|
| GRUMBACHER SYNVAR | 1672, 1672.CAN | Grumbacher Synvar |
| UTRECHT GLOSS OIL VARNISH | UT-11405 | 4 OZ, 118 ML |
| | UT-11406 | 8 OZ, 236 ML |
| | UT-11407 | 16 OZ, 473 ML |
| WEBER SYNVAR CLEAR GLOSS VARNISH | 1671 | 4 OZ, 118 ML |
| | 1672 | 8 OZ, 236 ML |
| | 1673 | 16 OZ, 473 ML |